


Technical Data Sheet

Properties of cast concrete mixtures

Cast concrete

is used for the production of spacers as well as sealing cones for tiebolt holes. The concrete used is a typical mix used for smaller precast items. Polypropylene fibres can be added to the mix to improve certain concrete properties.



Technical properties

Characteristics	Standard Mix	Premium Mix	SR-Mix	Notes
Compressive strength	> 50	> 60	> 50	N/mm²
Water absorption	< 8.0	< 5.0	< 8.0	% after 30 Min.
w/c factor	< 0,5	< 0,45	< 0,45	
Density	2,0-2,1	2,0-2,1	2,0-2,1	kg/dm³
Fire resistance class [EN 13501]	El30 – El180	El30 – El180	El30 – El180	
ASR (Alcali Silica reaction)	No reactivity			
Exposure class fulfilled	XC1 – XC4			
	XD1 – XD3			
	XS1 – XS3			
	XF1 – XF4 ¹			
		XA1		
	-	-	XA2 – XA3	CEM I 42,5 SR0 cement used ²
Additional notes		Silica fume ≥ 5,0% of the binder quantity		

Disclaimer / Notes:

All technical data stated in this TDS are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

Recommendations with regard to product application given in the present technical data sheet for practical assistance of product users are based on our experience and our present scientific and practical body of knowledge. These recommendations, however, are given without engagement and do not establish a contractual relationship or subsidiary duties. These recommendations do not relieve users of their liability and of their own responsibility to test, whether our product is adequate for the intended purpose of application. Please refer to the latest edition of this Technical Data Sheet on our web presence www.maxfrank.com

MAX FRANK Group

¹ Proof for exposure class XF4 via CDF-Test

² SR = Sulphate resistance; all requirements according to DIN 4030 fulfilled