

## Technical Data Sheet

### Zemseal® tape 50S

Double-sided, ready-to-use acrylic pressure sensitive adhesive tape on a roll for fixing Zemseal® fresh concrete membranes on vertical and/or inclined surfaces and for making overlaps on Zemseal® membranes



#### Product

<b>Description</b>	<b>Zemseal® adhesive tape 50S</b> is a tear-resistant, double-sided, ready-to-use acrylic adhesive film on a roll.
<b>Uses</b>	For fixing and installation of Zemseal® fresh concrete membranes on steel and composite formwork and other substrates. For making overlap joints of Zemseal® membranes.
<b>Characteristics / advantages</b>	<ul style="list-style-type: none"> <li>▪ permanently water resistant</li> <li>▪ very high resistance to aging</li> <li>▪ easy handling</li> </ul>

#### Product Data

<b>Appearance</b>	Acrylic adhesive film, double-sided adhesive on roll
<b>Packaging</b>	Roll length: 50 m Band width: 50 mm
<b>Storage</b>	<b>Zemseal® Adhesive Tape 50S</b> should be stored dry and protected from sunlight, at +5°C to +25°C.
<b>Material Properties</b>	Carrier: fabric Adhesive type Polyacrylate adhesive thickness 0,25 mm Adhesion 25 N / 25 mm Separating layer Polypropylene Very high tack to the touch Shear strength medium Temperature resistance -30°C to +100/120°C

#### Disclaimer / Notes:

All technical data stated in this TDS are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

Recommendations with regard to product application given in the present technical data sheet for practical assistance of product users are based on our experience and our present scientific and practical body of knowledge. These recommendations, however, are given without engagement and do not establish a contractual relationship or subsidiary duties. These recommendations do not relieve users of their liability and of their own responsibility to test, whether our product is adequate for the intended purpose of application. Please refer to the latest edition of this Technical Data Sheet on our web presence [www.maxfrank.com](http://www.maxfrank.com)