

EC Declaration of Performance




Brick-Track® Masonry Reinforcement

Product Identification: Brick-Track® BTG30	
<p>Manufacturer: Max Frank Ltd., Clough Street, Hanley, Stoke-on-Trent, Staffordshire, ST1 4AF Hereby declares that the product Brick-Track® conforms to the requirements of BS EN 845-3:2013 + A1:2016. Ladder-type steel welded wire meshwork for use as bed-joint reinforcement in masonry constructions. CE Mark in accordance with clause 4:2:2 of the standard.</p>	
Intended Use:	For structural applications in masonry walls.
Notified Body:	Lucideon Ltd, Queens Road, Penkhull, Stoke-on-Trent, Staffordshire, ST4 7LQ, UK.
Notified Body Number:	NB 1289

This product conforms to **System 3** – Assessment and Verification of Constancy of Performance.
 All testing was conducted at the above Notified Body.

Declared Performance:

Essential Requirement	Performance
Length (L) + Tol. (mm)	Standard: 2700 ± 1.5% L Varies: 2000 to 3000 ± 1.5%
Width (W) + Tol. (mm)	175 ± 5
Longitudinal Wire – Dia. + Tol. (mm)	3 ± 0.1
Equiv. Dia. of Flattened/Indented Wire Profile	2.75 ± 0.1
Cross Wire – Pitch + Tol. (mm)	450 ± 3%
Longitudinal Wire – Characteristic Yield Strength (N/mm ²)	600
Cross Wire – Characteristic Yield Strength (N/mm ²)	320
Bond Strength (N)	7917
Bond & Anchorage Length (mm)	450
Shear Load Capacity of Welds (N)	2500
Mortar Class	General purpose ≥ M4
Masonry Units (N/mm ²)	Compressive strength (fb) ≥ 5
Ductility Class – Tensile/Yield (AGT %)	Normal
Durability – Material Coating Reference	R13 Galvanised Steel
Dangerous Substances	None

	Authorised by:  Gerhard Bumes, Managing Director – Max Frank Ltd.	
---	--	---

Disclaimer: This information does not guarantee specific product features. Final determination of material suitability is the sole responsibility of the user.
 Doc. Ref: BTG30-W175/02–GBGB–05/19 Issued: 14/05/2019

Max Frank Limited

Clough Street | Hanley | Stoke-on-Trent | Staffordshire | ST1 4AF | Tel +44(0) 1782 598041

Registered Office: Max Frank Limited
 Clough Street, Hanley,
 Stoke-on-Trent, Staffordshire,
 ST1 4AF

Registered in England and Wales
 No. 6309165

VAT No.
 GB 921 456 534

www.maxfrank.com

EC Declaration of Performance




Brick-Track® Masonry Reinforcement

Product Identification: Brick-Track® BTG35	
Manufacturer: Max Frank Ltd., Clough Street, Hanley, Stoke-on-Trent, Staffordshire, ST1 4AF Hereby declares that the product Brick-Track® conforms to the requirements of BS EN 845-3:2013 + A1:2016. Ladder-type steel welded wire meshwork for use as bed-joint reinforcement in masonry constructions. CE Mark in accordance with clause 4:2:2 of the standard.	
Intended Use:	For structural applications in masonry walls.
Notified Body:	Lucideon Ltd, Queens Road, Penkhull, Stoke-on-Trent, Staffordshire, ST4 7LQ, UK.
Notified Body Number:	NB 1289

This product conforms to **System 3** – Assessment and Verification of Constancy of Performance.
All testing was conducted at the above Notified Body.

Declared Performance:

Essential Requirement	Performance
Length (L) + Tol. (mm)	Standard: 2700 ± 1.5% L Varies: 2000 to 3000 ± 1.5%
Width (W) + Tol. (mm)	175 ± 5
Longitudinal Wire – Dia. + Tol. (mm)	3.5 ± 0.1
Equiv. Dia. of Flattened/Indented Wire Profile	2.75 ± 0.1
Cross Wire – Pitch + Tol. (mm)	450 ± 3%
Longitudinal Wire – Characteristic Yield Strength (N/mm ²)	600
Cross Wire – Characteristic Yield Strength (N/mm ²)	320
Bond Strength (N)	7920
Bond & Anchorage Length (mm)	450
Shear Load Capacity of Welds (N)	2500
Mortar Class	General purpose ≥ M4
Masonry Units (N/mm ²)	Compressive strength (fb) ≥ 5
Ductility Class – Tensile/Yield (AGT %)	Normal
Durability – Material Coating Reference	R13 Galvanised Steel
Dangerous Substances	None

	Authorised by:  Gerhard Bumes, Managing Director – Max Frank Ltd.	
---	--	---

Disclaimer: This information does not guarantee specific product features. Final determination of material suitability is the sole responsibility of the user.
Doc. Ref: BTG35-W175/01-GBGB-05/19 Issued: 07/05/2019

Max Frank Limited

Clough Street | Hanley | Stoke-on-Trent | Staffordshire | ST1 4AF | Tel +44(0) 1782 598041

Registered Office: Max Frank Limited
Clough Street, Hanley,
Stoke-on-Trent, Staffordshire,
ST1 4AF

Registered in England and Wales
No. 6309165

VAT No.
GB 921 456 534

www.maxfrank.com

EC Declaration of Performance



Brick-Track® Masonry Reinforcement

Product Identification: Brick-Track® BTG40	
Manufacturer: Max Frank Ltd., Clough Street, Hanley, Stoke-on-Trent, Staffordshire, ST1 4AF Hereby declares that the product Brick-Track® conforms to the requirements of BS EN 845-3:2013 + A1:2016. Ladder-type steel welded wire meshwork for use as bed-joint reinforcement in masonry constructions. CE Mark in accordance with clause 4:2:2 of the standard.	
Intended Use:	For structural applications in masonry walls.
Notified Body:	Lucideon Ltd, Queens Road, Penkhull, Stoke-on-Trent, Staffordshire, ST4 7LQ, UK.
Notified Body Number:	NB 1289

This product conforms to **System 3** – Assessment and Verification of Constancy of Performance.
All testing was conducted at the above Notified Body.

Declared Performance:

Essential Requirement	Performance
Length (L) + Tol. (mm)	Standard: 2700 ± 1.5% L Varies: 2000 to 3000 ± 1.5%
Width (W) + Tol. (mm)	175 ± 5
Longitudinal Wire – Dia. + Tol. (mm)	4 ± 0.1
Equiv. Dia. of Flattened/Indented Wire Profile	2.75 ± 0.1
Cross Wire – Pitch + Tol. (mm)	450 ± 3%
Longitudinal Wire – Characteristic Yield Strength (N/mm ²)	600
Cross Wire – Characteristic Yield Strength (N/mm ²)	320
Bond Strength (N)	8540
Bond & Anchorage Length (mm)	450
Shear Load Capacity of Welds (N)	2500
Mortar Class	General purpose ≥ M4
Masonry Units (N/mm ²)	Compressive strength (fb) ≥ 5
Ductility Class – Tensile/Yield (AGT %)	Normal
Durability – Material Coating Reference	R13 Galvanised Steel
Dangerous Substances	None

	Authorised by:  Gerhard Bumes, Managing Director – Max Frank Ltd.	
---	--	---

Disclaimer: This information does not guarantee specific product features. Final determination of material suitability is the sole responsibility of the user.
Doc. Ref: BTG40-W175/01-GBGB-05/19 Issued: 07/05/2019

Max Frank Limited

Clough Street | Hanley | Stoke-on-Trent | Staffordshire | ST1 4AF | Tel +44(0) 1782 598041

Registered Office: Max Frank Limited
Clough Street, Hanley,
Stoke-on-Trent, Staffordshire,
ST1 4AF

Registered in England and Wales
No. 6309165

VAT No.
GB 921 456 534

www.maxfrank.com

EC Declaration of Performance




Brick-Track® Masonry Reinforcement

Product Identification: Brick-Track® BTG45	
Manufacturer: Max Frank Ltd., Clough Street, Hanley, Stoke-on-Trent, Staffordshire, ST1 4AF Hereby declares that the product Brick-Track® conforms to the requirements of BS EN 845-3:2013 + A1:2016. Ladder-type steel welded wire meshwork for use as bed-joint reinforcement in masonry constructions. CE Mark in accordance with clause 4:2:2 of the standard.	
Intended Use:	For structural applications in masonry walls.
Notified Body:	Lucideon Ltd, Queens Road, Penkhull, Stoke-on-Trent, Staffordshire, ST4 7LQ, UK.
Notified Body Number:	NB 1289

This product conforms to **System 3** – Assessment and Verification of Constancy of Performance.
All testing was conducted at the above Notified Body.

Declared Performance:

Essential Requirement	Performance
Length (L) + Tol. (mm)	Standard: 2700 ± 1.5% L Varies: 2000 to 3000 ± 1.5%
Width (W) + Tol. (mm)	175 ± 5
Longitudinal Wire – Dia. + Tol. (mm)	4.5 ± 0.1
Equiv. Dia. of Flattened/Indented Wire Profile	2.75 ± 0.1
Cross Wire – Pitch + Tol. (mm)	450 ± 3%
Longitudinal Wire – Characteristic Yield Strength (N/mm ²)	600
Cross Wire – Characteristic Yield Strength (N/mm ²)	320
Bond Strength (N)	8540
Bond & Anchorage Length (mm)	450
Shear Load Capacity of Welds (N)	2500
Mortar Class	General purpose ≥ M4
Masonry Units (N/mm ²)	Compressive strength (fb) ≥ 5
Ductility Class – Tensile/Yield (AGT %)	Normal
Durability – Material Coating Reference	R13 Galvanised Steel
Dangerous Substances	None

	Authorised by:  Gerhard Bumes, Managing Director – Max Frank Ltd.	
---	--	---

Disclaimer: This information does not guarantee specific product features. Final determination of material suitability is the sole responsibility of the user.
Doc. Ref: BTG45-W175/01-GBGB-05/19 Issued: 07/05/2019

Max Frank Limited

Clough Street | Hanley | Stoke-on-Trent | Staffordshire | ST1 4AF | Tel +44(0) 1782 598041

Registered Office: Max Frank Limited
Clough Street, Hanley,
Stoke-on-Trent, Staffordshire,
ST1 4AF

Registered in England and Wales
No. 6309165

VAT No.
GB 921 456 534

www.maxfrank.com

EC Declaration of Performance

Brick-Track® Masonry Reinforcement

Product Identification: Brick-Track® BTG50	
<p>Manufacturer: Max Frank Ltd., Clough Street, Hanley, Stoke-on-Trent, Staffordshire, ST1 4AF Hereby declares that the product Brick-Track® conforms to the requirements of BS EN 845-3:2013 + A1:2016. Ladder-type steel welded wire meshwork for use as bed-joint reinforcement in masonry constructions. CE Mark in accordance with clause 4:2:2 of the standard.</p>	
Intended Use:	For structural applications in masonry walls.
Notified Body:	Lucideon Ltd, Queens Road, Penkhull, Stoke-on-Trent, Staffordshire, ST4 7LQ, UK.
Notified Body Number:	NB 1289

This product conforms to **System 3** – Assessment and Verification of Constancy of Performance.
 All testing was conducted at the above Notified Body.

Declared Performance:

Essential Requirement	Performance
Length (L) + Tol. (mm)	Standard: 2700 ± 1.5% L Varies: 2000 to 3000 ± 1.5%
Width (W) + Tol. (mm)	175 ± 5
Longitudinal Wire – Dia. + Tol. (mm)	5 ± 0.1
Equiv. Dia. of Flattened/Indented Wire Profile	2.75 ± 0.1
Cross Wire – Pitch + Tol. (mm)	450 ± 3%
Longitudinal Wire – Characteristic Yield Strength (N/mm ²)	600
Cross Wire – Characteristic Yield Strength (N/mm ²)	320
Bond Strength (N)	10250
Bond & Anchorage Length (mm)	450
Shear Load Capacity of Welds (N)	2500
Mortar Class	General purpose ≥ M4
Masonry Units (N/mm ²)	Compressive strength (fb) ≥ 5
Ductility Class – Tensile/Yield (AGT %)	Normal
Durability – Material Coating Reference	R13 Galvanised Steel
Dangerous Substances	None

	<p>Authorised by:</p>  Gerhard Bumes, Managing Director – Max Frank Ltd.	
---	--	---

Disclaimer: This information does not guarantee specific product features. Final determination of material suitability is the sole responsibility of the user.
 Doc. Ref: BTG50-W175/02–GBGB–05/19 Issued: 14/05/2019

Max Frank Limited

Clough Street | Hanley | Stoke-on-Trent | Staffordshire | ST1 4AF | Tel +44(0) 1782 598041

Registered Office: Max Frank Limited
 Clough Street, Hanley,
 Stoke-on-Trent, Staffordshire,
 ST1 4AF

Registered in England and Wales
 No. 6309165

VAT No.
 GB 921 456 534

www.maxfrank.com