

Declaration of Performance

Annex III of regulation (EU) Nr. 305/2011



Intectin® Plus (IPUP01)



<p>1. Product Type: Unique identification code of the product type</p>	<p>Intectin® Plus</p>
<p>2. Type: Batch or serial number or any other element allowing identification of the construction product as required under Article 11(4)</p>	<p>Refer to product label</p>
<p>3. Intended use: Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer</p>	<p>Concrete injection for ductile filling of cracks (D) U (D1) W (2) (1/2/3/4) (5/40)</p>
<p>4. Name, registered trade name: Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5)</p>	<p>Intectin® Plus Max Frank GmbH & Co. KG Mitterweg 1 94339 Leiblfing, Germany</p>
<p>5. Contact address: Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2)</p>	<p>Not relevant (see 4)</p>
<p>6. AVCP: System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V</p>	<p>System 2+ (for uses in buildings and civil engineering works)</p>
<p>7. Notified body (hEN): In case of the declaration of performance (DoP) concerning a construction product covered by a harmonized standard</p>	<p>Karlsruher Institut für Technologie (KIT) 0754 – CPR – 15-0399</p>
<p>8. Notified body (ETA): In case of the declaration of performance concerning a construction product for which an ETA has been issued</p>	<p>not applicable</p>

9. Declared Performance:

Basic Characteristics	Performance	Harmonized technical specification
Adhesion	0,39 – 0,89 N/mm ²	EN 1504-5: 2004
Elongation	> 10 %	
Watertightness	D1	
Glass transition temperature	- 4,2 °C	
Injectability into dry medium	0,1 mm	
Injectability into non-dry medium	0,2 mm	
Durability (Compatibility with concrete)	No failure in compression, lost deformation work < 20 %.	
Corrosion behaviour	It is assumed that no corrosive effects are present.	
Release of dangerous substances	EN 1504-5, Art. 5.4	

10. Declaration:

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by



.....
 Moritz Michel
 Dipl. - Ing. B.Sc. Moritz Michel
 Head of Technical Product Management

Leiblfing, 1st October 2019