

## Declaration of Performance

Annex III of regulation (EU) Nr. 305/2011



## Sorp Acoustic Plaster

Sorp Acoustic Plaster is an almost sound-transparent final coating for use on concrete ceilings in which the Sorp10® sound absorber has been installed.



<b>1. Product Type:</b> Unique identification code of the product type	<b>Plaster with organic binders</b> SORPSP02
<b>2. Type:</b> Batch or serial number or any other element allowing identification of the construction product as required under Article 11(4)	<b>Batch number:</b> refer to product label
<b>3. Intended use:</b> Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer	<b>For interior use for walls, columns, partition walls and ceilings</b> According to EN 15824:2017
<b>4. Name, registered trade name:</b> Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5)	<b>Sorp Acoustic Plaster</b> Max Frank GmbH & Co. KG, Mitterweg 1, 94339 Leiblfing, Germany
<b>5. Contact address:</b> Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2)	<b>not relevant</b> – see no.4
<b>6. AVCP:</b> System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V	<b>System 4</b> <b>System 3 for reaction to fire</b>
<b>7. Notified body (hEN):</b> In case of the declaration of performance (DoP) concerning a construction product covered by a harmonized standard	The notified body "MPA Dresden" with the identification no. 0767 has carried out the reaction to fire test according to system 3 and issued the following:  Classification report no. 20160162/01.1 Test report no. 20160162/02.2 and 20160162/03.3

---

**8. Notified body (ETA):** not relevant

In case of the declaration of performance concerning a construction product for which an ETA has been issued

---

**9. Declared performance:**

**Essential characteristics**

adhesive strength  
thermal conductivity  
reaction to fire  
dangerous substances

**Performance**

≥ 0.3 MPa  
NPD  
class A2-s2, d0  
NPD

---

**10. Declaration:**

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by



.....  
Dipl. - Ing. B.Sc. Moritz Michel

Head of Technical Product Management

Leiblfing, 11th September 2019

---